



## GYM FINISH 25

### Description:

Polyurethane water based finish designed for wood floors, especially for gym floors.

### Intended Use:

Recommended for high traffic public areas schools and all commercial buildings with wood floors.

### Product Features:

- Durable Finish
- Water Based
- Exceptional Performance Under Heavy Usage

### Physical Properties:

- Flash Point..... n/a
- Viscosity..... [CPS] (30-70)
- Color..... Milky
- Type of Solids..... 28%
- Boiling Point..... 212°F (100°C)
- Fragrances..... Mild
- pH..... 7.0 - 8.5

### Limitations of Use:

For residential/professional use.

### Customer Service:

Call or Visit West Coast Chemical  
Toll Free: 1.800.223.0526  
E-mail: westcoastchemical@yahoo.com

### Surface Preparation:

New wood should be sealed with an acrylic sealer before applying gym finish 25. recoating requires sanding. Mamp mopping and vacuuming.

### Mixing Instructions:

Add 2oz of cross linker to each gallon of Gym Finish before applying.

### Application Instructions:

A thorough tacking is required before applying gym finish 25, apply with a padco applicator and allow 3-4 hours drying time between coats. 2-3 coats are generally adequate for excellent appearance and long term wear. Recoating without sanding can be done up to 4 hours after applying a coat sanding between coats, however, provides the best film appearance.

### Storage:

- Do not allow to freeze.
- Keep containers closed when not in use and upright to prevent leaking.

### Compliances:

Contains no volatile organic components.

### Chemical Resistance:

N/A

### Precautions:

Please refer to the appropriate material safety data sheet (MSDS) prior to using this product.

For technical assistance, please call 1.800.223.0526  
FOR INDUSTRIAL / PROFESSIONAL USE ONLY

Keep containers closed when not in use and upright to prevent leaking. DO NOT take internally. Wash hands after using and before eating. Keep out of reach of children. Dispose of according to law and local regulations.