



PARAGON II

Description:

An Aliphatic Two –Part , High Gloss , Non-Yellowing Urethane Ultra Durable floor coating that delivers performance and cost –effectiveness that far surpasses the performances of conventional floor finishes. PARAGON II ONE HOUR DRY TIME.

Intended Use:

Recommended for all hard surfaces including sheet vinyl, linoleum, vct, terazzo, granite, marble, quarry tile, wood and many other types of flooring.

Product Features:

- Fast Dry Time One Hour
- Pot Life 8 Hours
- Improve SCOF Slip Resistance
- Water Based Environmentally Safe
- Low VOC {98g/1}
- Reduced floor interventions eliminating strippers. Excellent abrasion resistance/ gloss retention
- Mar & Abrasion Resistant
- Acid & Chemical Resistant
- Replaces Acrylic Finishes
- Eliminates Burnishing
- Superior Stain Resistance
- Superior solvent { MEK, Ethanol} and 100 degree C water Resistance

Physical Properties:

- Solids..... 30%
- Viscosity..... 5-10
- Tensile Strength..... 4400
- UVA-340 gloss loss.. 2%
- Tack Free Time..... 30-35
- Pot Life..... 8 HRS
- pH..... 8.0

Limitations of Use:

For residential/professional use.

Customer Service:

Call or Visit West Coast Chemical
Toll Free: 1.800.223.0526
E-mail: westcoastchemical@yahoo.com

Surface Preparation:

Strip and remove all old coating material from the surface and rinse thoroughly with clear water. Apply two coats of New Life Sealer allow thirty minutes between coats.

Recoating Existing Urethane Finish:

Screen the existing urethane with a 120 grit screen thoroughly and rinse afterwards with clean water. Apply two coats of New Life Sealer allow thirty minutes between coats.

Mixing Instructions:

Add part B catalyst into part A resin mix thoroughly for 30 seconds. Allow the mixed products to stand for 30 minutes before applying. Note: Do not cover mixed product A/B it generates CO₂.

Application Instructions:

For best results pour Paragon II on the surface and spread with a microfiber applicator maintain even heavy flow and make sure to keep a wet edge continuously. Experienced applicators tape off the finish line to prevent any over spill. A second coat may be applied in one hour or as soon as the coat is dry, normally in one hour.

Storage:

- Do not allow to freeze.
- Keep containers closed when not in use and upright to prevent leaking.

Compliances:

Contains no volatile organic components.

Chemical Resistance:

N/A

Precautions:

Please refer to the appropriate material safety data sheet (MSDS) prior to using this product.

For technical assistance, please call 1.800.223.0526
FOR INDUSTRIAL / PROFESSIONAL USE ONLY

Keep containers closed when not in use and upright to prevent leaking. DO NOT take internally. Wash hands after using and before eating. Keep out of reach of children. Dispose of according to law and local regulations.